

12.8V 206Ah LITHIUM BATTERY




► Features

- A grade brand new prismatic LiFePO4 cells
- > 4000 cycles @80% DOD(25°C, 0.5C)
- Over charge, over discharge, over temperature, low temperature, over current and short circuit protection
- Easy installation and maintenance free
- Cell balance function
- ABS Case, corrosion and high temperature resistance
- Certificate:UN38.3 MSDS IEC62619 CE-RED ROHS
- Max 4 battery packs can be connected in series/parallel


► Electrical Characteristics

Model	LFP2.56KWH12.8V-P65L2-Colombia
Battery Type	LiFePO4
Nominal Voltage (V)	12.8
Nominal Capacity (AH)	206
Energy (WH)	2637
Pack Mode	4S2P
Continuous Discharge Current (A)	100
Charge Cut-off Voltage (V)	14.4
Discharge Cut-off Voltage (V)	10.4
Max.Charge Current (A)	100
Max.Discharge Current (A)	200
Peak Discharge Current (A)	240@10S
Recommend Discharge Current (A)	100
Recommend Discharge Depth (%)	80
Cycle Life	> 4000 cycles (25°C, 0.5C) 80% DOD
function	Bluetooth
Display	---
Charge&Discharge Temperature (°C)	Charge: 0°C~+50°C / Discharge: -20°C~+60°C
Optimal Storage Temperature (°C)	5°C ~ +35°C
Recommend Storage Humidity	20%~80%
Terminal	M8
Dimensions (L*W*H) (mm)	522*268*218
Weight (Kg)	23.1±0.5
Transportation	UN38.3 MSDS IEC62619 CE-RED ROHS
IP Class	IP65


Different Rate Discharge Curve@25°C




Different Temperature Discharge Curve0.5C




State of Charge Curve@0.5C 25°C



Charging Characteristics@0.5C 25°C



Different DOD Discharge Cycle Life Curve@0.5C 25°C



Different Temperature Self Discharge Curve

