


► Product Appearance




► Product Size



Net Weight: 40.9±0.5kg

► Packaging Size



Gross Weight: 44.1±0.5kg


► Features

- A grade brand new prismatic LiFePO₄ cells
- >4000 cycles @80% DOD(25°C, 0.5C)
- Over charge, over discharge, over temperature, low temperature, over current and short circuit protection
- Easy installation and maintenance free
- Cell balance function
- ABS Case, corrosion and high temperature resistance
- Certificate: UN38.3, MSDS, IEC62619, CE-RED, ROHS
- Max 4 battery packs can be connected in series/parallel


► Electrical Characteristics

Model	LFP5.12KWH25.6V-P65L2GF40
Electrical Parameter	
Battery type	LiFePO4
Nominal voltage	25.6V
Nominal capacity	205Ah
Energy	5248Wh
Pack mode	8S1P
Continuous discharge current	100A
Charge cut-off voltage	28.8V
Discharge cut-off voltage	20.8V
Max. charge current	100A
Max. discharge current	200A
Peak discharge current	240A
Recommend discharge current	100A
Recommend discharge depth	80%
Cycle life	> 4000 cycles (25°C, 0.5C) 80% DOD
Function	Bluetooth, heating
Environmental Parameter	
Charge & discharge temperature	Charge: 0°C~+55°C Discharge: -20°C~+60°C
Optimal storage temperature	5°C ~ +35°C
Relative humidity	40%-80%
Ingress protection	IP65
Mechanical Parameter	
Terminal	M8
Dimensions (LxWxH) (mm)	636x245x218
Weight (Kg)	40.7±0.5
Certificate	UN38.3, MSDS, IEC62619, CE-RED, ROHS


Different Rate Discharge Curve@25°C




Different Temperature Discharge Curve@0.5C




State of Charge Curve@0.5C 25°C



Charging Characteristics @0.5C 25°C



Different DOD Discharge Cycle Life Curve@0.5C 25°C



Different Temperature Self Discharge Curve

