


► Product Appearance




► Product Size



Net Weight: 26.1±0.5kg

► Packaging Size



Gross Weight: 28.6±0.5kg


► Features

- A grade brand new prismatic LiFePO₄ cells
- > 4000 cycles @80% DOD(25°C, 0.5C)
- Over charge, over discharge, over temperature, low temperature, over current and short circuit protection
- LED less power consumption, high brightness, long visual distance
- Cell balance function
- Rack-mounted style
- Certificate: UN38.3, MSDS, IEC62619
- Max 8 battery packs can be connected in parallel


► Electrical Characteristics

Model		LFP2.4KWH48V- P20R1GT40
Electrical Parameter		
Battery type		LiFePO ₄
Nominal voltage		48V
Nominal capacity		52Ah
Energy		2496Wh
Pack mode		15S1P
Continuous discharge current		25A
Charge cut-off voltage		54V
Discharge cut-off voltage		39V
Max. charge current		25A
Max. discharge current		50A
Peak discharge current		60A
Recommend discharge current		25A
Recommend discharge depth		80%
Cycle life		> 4000 cycles (25°C, 0.5C) 80% DOD
Communication		RS485/RS232/CAN
Display		LED
Environmental Parameter		
Charge & discharge temperature		Charge: 0°C~+55°C Discharge: -20°C~+60°C
Optimal storage temperature		5°C ~ +35°C
Relative humidity		40%-80%
Ingress protection		IP20
Mechanical Parameter		
Terminal		M6
Dimensions (WxHxD) (mm)		426x340x150
Weight (Kg)		26.1±0.5
Certificate		UN38.3, MSDS, IEC62619


Different Rate Discharge Curve@25°C




Different Temperature Discharge Curve@0.5C




State of Charge Curve@0.5C 25°C



Charging Characteristics @0.5C 25°C



Different DOD Discharge Cycle Life Curve@0.5C 25°C



Different Temperature Self Discharge Curve

